

# Pulsar XCD 125 CC

| PERIODIC PARTS REPLACEMENT   |       |       |       |       |        | 2011   |
|--|-------|-------|-------|-------|--------|--|
| SCHEDULE   |       |       |       |       |        |  |
| XCD 125 CC   |       |       |       |       |        |  |
| Km   | 750   | 2,500 | 5,000 | 7,500 | 10,000 | Subsequent Km  |
| Days   | 30    | 90    | 180   | 270   | 360    |  |
| Engine Oil<br>SAE 20W40 +<br>API "SJ" JASO<br>"MA"<br>1000 ml      | G     |       | G     |       | G      | *G at every 5,000 Km   |
| Paper oil filter   | G     | B     | G     | B     | G      | *B at every 2,500 Km<br>*G at every 10,000 Km  |
| Spark plug (Qty 2)   | B & S | B & S | B & S | B & S | G      | *G at every 10,000 Km  |
| Front fork oil (330 ml)  |       |       |       |       | G      | *G at every 10,000 Km  |
| Starter Clutch Bush  |       |       |       |       | G      | *G at every 10,000 Km  |
| Brake Shoes  |       |       | P     | P     | G      | *G if shoe thickness comes tp 2.0 mm   |
| Front disk pad   |       |       | P     | P     | G      | *G if pad thickness comes to 3.8 mm  |
| Drive Chain lock & link set  |       |       |       |       | G      | *G at every 10,000 Km  |
| Streering Cone kit   |       |       |       |       | G      | *G at every 15,000Km   |
| Clutch plate   |       |       |       |       |        | *G at every 20,000Km   |
| Rear brake damper  |       |       |       |       | B      | *P for noise by rotating rear wheel at every 10,000 Km; G (if necessary)<br>*G at every 20,000Km |
| Chain Sprocket Kit   | L     | L/S   | L/S   | L/S   | L/S    | *P & S slackness at every 2,500 Km<br>*G at every 20,000Km                                       |
| Carburetor insulator   |       |       |       |       |        | *G at every 25,000Km   |
| Valve oil kit  |       |       |       |       |        | *G at every 30,000Km   |
| G-Ganti      B-Bersihkan      P-Periksa      L-Lumasi      S-Setel |       |       |       |       |        |  |